

## IP400

### General

|                                  |   |
|----------------------------------|---|
| Average compacted bag weight     | 16-18kg   |
| Average compacted package        | 375mm x 375mm x 380mm                                     |
|                                  | 55 litre  |
| Compaction force                 | 3000kgf   |
| Compaction ratio                 | 5:1   |
| Cycle time                       | 14 seconds (including 4 second delay at bottom of stroke) |
| Dimensions Compactor (h x w x d) | 1645mm x 580mm x 600mm                                    |
| Dimensions Trolley (h x w x d)   | 600mm x 410mm x 550mm                                     |

### Electrical information

|                              |   |
|------------------------------|---|
| Motor                        | 0.75kW (1HP)                            |
| Voltages*                    | 230-1-50                                |
| Fuse rating                  | 1 phase (13A)                           |
| Controls                     | 24V                                     |
| Operator controls/indicators | On/Off key ensures authorised operation |
|                              | Stop and start buttons                  |
|                              | Normal/constant operating mode switch   |
|                              | Machine run indicator light             |
|                              | Bag full indicator light                |

### Installation information

|                       |  |
|-----------------------|--|
| General               | A level floor area 600mm x 600mm is required plus additional space to pull out trolley bin |
| Electrical connection | 2.5m cable with 13A plug   |

### Features

|                  |   |
|------------------|---|
| Operating modes  | Single stroke                                   |
|                  | Constant pressure setting (night position)      |
| Operator safety  | Interlock on waste-in chute                     |
|                  | Interlock on trolley bin                        |
| Special features | Wheeled trolley bin for easy movement           |
|                  | 100 plastic bags, wire ties and tying tool      |
|                  | Stainless steel trolley liners for bag rigidity |

### Customer Options

|  |                                    |
|--|------------------------------------|
|  | Additional trolleys                |
|  | Lift-A-Pak                         |
|  | Deck Feet for marine installations |

### Product code details

|         |   |
|---------|---|
| F56/400 | IP400 Compactor 1 phase                   |
| S56/049 | Additional trolley                        |
| S56/059 | Additional 100 plastic bags and wire ties |
| **      | Deck Feet for marine installations        |

### Shipping specification

|                                |   |
|--------------------------------|---|
| Packing dimensions (h x w x d) | 1760mm x 600mm x 730mm                                |
| Packing volume                 | 0.770m <sup>3</sup>                                   |
| Packing weight (gross/net)     | 223kg/193kg   |
|                                | (Extra trolley shipping specification on application) |

\* Marine voltages available on request

\*\* To be specified when ordering unit