



WMB5FX/PB/B - Lincat FilterFlow WMB Wall Mounted Automatic Fill Push Button Boiler - Black Glass - 5L Capacity - 3.0 kW

The FilterFlow Wall Mounted WMB5FX/PB Water Boiler offers the benefits of great efficiencies, convenient touchscreen operation in a sleek glass wall mounted design.

- ✔ Push button operation, ideal for self-service and front of house applications
- ✔ Easily operated from a large, colour touchscreen display
- ✔ High quality boiling water on tap 24 hours a day
- ✔ Built-in water filtration system improves water quality and reduces scale build-up
- ✔ High volume, easy change FilterFlow cartridge
- ✔ Adjustable water temperature from 70-98°C, ideal for all types of beverage
- ✔ Precise electronic temperature control system
- ✔ Boiler operation can be timed to switch off overnight, to save energy when not in use
- ✔ Enhanced multi-level diagnostics - enable the engineer to identify the parts needed, and repair the water boiler at first visit

Specifications

| Summary | | Power and Performance | |
|-----------------------------|-----------------------------------|-----------------------------|-------|
| Brand | Lincat | Total Power kW | 3 |
| Range | FilterFlow | Temperature Range °C | 70-98 |
| Series | WMB Wall-mounted Boiler | IP Rating | IP23 |
| Power Type | Electric | Hourly Output Litres | 28 |
| Unit Type | Wall-mounted | Hourly Output Cups | 140 |
| Available in UK Only | No | | |
| UK Warranty | 2 Years Parts and Labour Warranty | | |
| Export Warranty | Contact your local dealer | | |
| GTIN | 5056105121817 | | |

| Key Specifications | | Capacity | |
|----------------------|----------------------------|----------------------------------|-----|
| Outlet | Push Button [Single Spout] | Hot and Cold Water Output | No |
| Dispense Lock | No | Rapid Draw Off Litres | 5.5 |
| WRAS Approved | No | Rapid Draw Off Cups | 28 |
| | | Capacity Litres | 5 |

| Weights and Dimensions | | Supply Connections | |
|----------------------------------|------|---------------------------------------|---------|
| Unit Height (External) mm | 464 | Requires Installation | Yes |
| Unit Width (External) mm | 353 | Requires Electrical Supply | Yes |
| Unit Depth (External) mm | 218 | UK 3 Pin Plug | No |
| Net Weight Kg | 12.6 | Requires Hardwiring | Yes |
| | | Electrical Supply Rating Watts | 3,000 |
| | | Single Phase Amps | 13 |
| | | Single Phase Voltage | 230 |
| | | Water Connection Pressure Bar | 1.0-8.0 |
| | | Water Connection | 3/4" |

Shipping

| | |
|-------------------------|-------|
| Packed Weight Kg | 13.86 |
| Packed Height cm | 40 |
| Packed Width cm | 42 |
| Packed Depth cm | 65 |

Available Accessories

| | |
|-------------|---|
| DP10 | Descaler Powder |
| DR97 | Drip Tray for FilterFlow WMB5FX/PB |
| FC04 | Filter Cartridge for Lincat FilterFlow Water Boiler |



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm